

PRODUCT SPECIFICATIONS FOR ROLLED FORM SPLINT

Purpose: Immobilize patient extremities.

Description: Rolled form splints are composed of layers of knitted fiber glass fabric coated with a urethane resin that hardens when exposed to water. These layers of coated fiber glass are enclosed within a polypropylene nonwoven padding. The complete splint is then sealed in a moisture/air proof foil pouch.

Use: A length of splint is removed from the foil and cut to the required length. The foil is then resealed with the clamp which is included with each splint. Water is then applied to the short section of splint and the water is then removed through squeezing the splint enclosed in a towel. The splint is then shaped and applied to the patient.

Product:

Item	Fabric Layers	Size
PRO1102-1	5 LAYERS K616003	2" x 15 FEET
PRO1103-1	7 LAYERS K616003	3" X 15 FEET
PRO1104-1	7 LAYERS K616003	4" X 15 FEET
PRO1105-1	7 LAYERS K616003	5" X 15 FEET
PRO1106-1	7 LAYERS K616003	6" X 15 FEET

Width tolerance: +/- 1/4 inch

Length tolerance: +/- 3 inches

Labeling:

Each splint roll shall have a manufactured date of the type MMDDYY affixed to the foil. Each individual dispensing carton will have the same manufactured date applied.

Packaging:

Each foil roll will be boxed individually in a dispensing carton of appropriate width. Rolled form splints will be shipped two dispensing cartons per case. Single wall corrugated packaging gross weight limit is 65 pounds.

Storage:

The splints should be stored in a cool dry location.

Recommended storage temperature: 65F- 75F/ 18C- 24C